



<p>Rough Wall Opening 15-5/8" (397mm) wide 29-1/8" (740mm) high 4" (102mm) minimum recessed depth</p>
--

CONSTRUCTION:

Fabricated of type 304 heavy-gauge stainless steel. All welded construction with exposed surfaces having a #4 satin-finish. One piece seamless 22-gauge (0.8mm) flange provided with 1/4" (6mm) return for rigidity. 1/4" (6mm) float/plate mirror mounted 15° Fixed-Position Tilt door mounted on a continuous stainless steel piano-hinge and provided with a tumbler lock. Door provided with door retainer. All purpose valve provided. Cabinet is all welded construction.

CAPACITY:

600 C-fold or 800 multi-fold towels. 1-gallon (2.8-L) soap dispenser filled by opening tumbler locked cover. 100 - 3-fl oz. (0.1-L) paper cups.

OVERALL DIMENSIONS:

17-1/8" W x 30-5/8" H x 4" D (435 x 778 x 102mm)

MOUNTING:

Bottom edge of reflective surface should be mounted no higher than 40" (1016mm) above the finish floor. 74" (1880mm) to top of unit. Full length mirrors will accommodate all facilities. Mounting location for push button dispensers are 44" (1118mm) maximum above the finished floor. Push buttons and pistons should be operable with one hand and without tight grasping, pinching, or twisting of the wrist. Activation of soap valves should not require more than 5 pounds of force when unit is completely filled.

Recessed Multi-Purpose Unit with Fixed-Position Tilt shall be Model MPU-5 of Gamco Commercial Restroom Accessories, A Division of Bobrick, One Gamco Place, Durant, OK